

PERFORATED WHITE OBSCURED VISION (HD)



Description

Micro perforated privacy window film which appears translucent white from both sides. It provides good one-way vision privacy during daytime and helps to obscure the view into buildings at night (with the right internal lighting - see main image)..



Colour

Translucent White



Surface type

Micro Perforated



Installation

Inside or Outside Window

Privacy characteristics



DAY: Excellent (*)

NIGHT: Some Privacy

VIEW OUT: Good (milky)



On window durability

3 Years+



Storage (22°C, 55% humidity)

2 Years



Environmental standard

REACH compliant

Roll Sizes Available

10metres (length) x 1370mm (width)

30metres (length) x 1370mm (width)

(*) A low level of privacy will be given if there is more light on the inside than on the outside of the window, e.g. if the inside is illuminated at night.

Technical Specification

Face film	Translucent white polymeric PVC
Thickness	180micron +/- 10
Hole pattern	40% micro perforated; 1.0mm diameter holes
Adhesive	Transparent, semi-permanent
Protective release liner	Silicone coated paper
Min appl temp	4°C.

Installation Recommendations

For vertical installation on standard glass. Apply using a dry application method. Glass must be thoroughly cleaned beforehand with soap and water. Rinse and dry glass after cleaning.

Not to be applied to fresh paint or ink, polycarbonate, rubber, plastic moldings and certain PVCs. In case of doubt, please test prior to final application.

This product is not recommended for use around a sharp angle where there is a limited area either side of the angle.

The film must not touch the rubber window moulding. Not to be washed within 24 hours

x Not recommended for use on glass with coatings such as anti-reflective, self-cleaning and scratch-resistance

Solar Properties

Data calculated based on film applied to inside of clear glass 3mm thick.

Visible light transmission	49%
Visible light reflection, exterior	34%
Visible light reflection, interior	29%
UV transmission	28%
Solar energy transmission	46%
Solar energy reflection	28%
Solar energy absorption (total)	26%
Glare reduction (relative %)	60%
g value	0.57
Shading coefficient (SC)	0.66

Contact Information

Contra Vision Supplies Ltd,
 Victoria House 19-21 Ack Lane East,
 Bramhall, Stockport, SK7 2BE,
 United Kingdom
 Tel. +44 161 439 9307
 Email: sales@contravision.com
 Web: www.contravision.com

This document is intended as a source of information, is given without guarantee, and does not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of the product for their specific intended purpose.

Maintenance care

Wash with soapy water. Gently wipe with lint cloth or soft bristled brush to remove grease and dirt. Take particular care not to damage the edges and corners. Wash off suds and leave to dry.